

MODEL #

XSEBIP8MP28-AI+

CTAVUE® BY



ULTRA SERIES AI+ **SPECTRAL CAMERA**

Onvif® | GMST | NDAA Compliant | AI



8MP
RESOLUTION



8MP
Resolution

2.8MM
Lens



IR Up to
25M



See In Full Color
At Night



Two-Way
Communication



Audio/Alarm
In/Out



IP67
Waterproof &
Dustproof



Micro SD Card
Slot up to 1TB

Introducing the **XSEBATVIP8MP28-AI+**, a high-performance security camera designed to deliver reliable monitoring and clear video quality in various environments. Providing real-time video output at a maximum resolution of 3840x2160@30fps, it ensures detailed and smooth surveillance for everyday security applications. Equipped with AI-ISP technology, the camera delivers excellent noise reduction, improving image clarity even in challenging lighting conditions. With intelligent analytics, it enhances monitoring capabilities for smarter and more efficient surveillance. Designed for flexible lighting environments, the camera supports warm light and infrared dual supplementary lighting, ensuring effective monitoring both day and night. It also supports backlight compensation, strong light suppression, 3D digital noise reduction, and a 120dB wide dynamic range, making it suitable for different video environments while maintaining balanced image quality. For added functionality, the device is equipped with 1 built-in microphone and 1 built-in speaker, enabling audio support for monitoring applications. Built for durability, it is designed to meet IP67 dust and water resistance standards, ensuring reliable performance in both indoor and outdoor conditions.

WWW.GSDGROUPINC.COM



A CANADIAN ENTERPRISE

2025 Global Surveillance Distribution. G.S.D. Group, and G.S.D. are registered trade names of Global Surveillance Distribution Group, Inc., a corporation under the laws of Canada and other jurisdictions. We reserve the right to change product designs, specifications, and features without notice or liability. Information is subject to change and is not guaranteed for accuracy or completeness.

VIDEO

Image Sensor	1/1.8"
Max. Resolution	8MP 3840(H)×2160(V)@30fps
Min. Illumination	Color 0.0007lux @ F1.0(AGC ON) ; B/W 0 lux @ IR ON
Scanning System	Progressive CMOS

LENS

Focal Length	2.8 mm
Aperture	F1.0
Angular Field of View	Horizontal:110° Vertical:60° Diagonal:113°
Min. Object Distance	2.5m

OPERATIONAL

IR LED	1
Warmlight	2
Red Blue Light	2(1 Red&1 Blue)
IR Viewable Length	Up to 25m
Warm Light Viewable Length	Up to 20m
Type of complementary light	Default warm light, switchable infrared light
Motion Detection	Off/On (8 Level)
Wide Dynamic Range	WDR
Digital Noise Reduction	3D DNR
Image Setting	Full Color Mode/Day&Night Mode/Smart Illumination
White Balance	Auto/Manual
Electronic Shutter Speed	1/5 ~ 1/20000s
Edge Storage	Micro SD slot, up to 1TB
Alarm	NA
Audio	Built-in microphone&Speaker
Custom Voice	Yes
Hardware Reset	Yes
AI Feature	Face Recognition, Pedestrian & Vehicle, Perimeter Intrusion, Multi-Target-Type Recognition, Line Crossing, Object Detection, Crossing Counting, Heat Map, Crowd Density, Queue Length, License Plate, Rare Sound, Intrusion, Region Entrance, Region Exiting, Fall Detection, Fire&Smoke Detection


NETWORK

Ethernet	RJ45(10/100BASE-T)
Video Compression	H.265/H.264/H.265+/H.264+/MJPEG
Resolution	Mainstream@30fps 8MP(3840x2160),5MP(2592x1944,3072x1728), 4MP(2592x1520),3MP(2304x1296),1080P(1920x1080),960P(1280*960),720P(1280x720) Substream@30fps 720P(1280x720),VGA(640x480),QVGA(320x240) Mobilestream@30fps VGA(640x480), QVGA(320x240)
Video Quality Adjustment	256Kbps ~ 16Mbps
Bitrate control method	CBR/VBR
IP	IPV6
Protocol	TCP/IP,HTTP,DHCP,DNS,DDNS,RTP/RTSP,SMTP,NTP,UPnP,SNMP,HTTPS,FTP
Security	IP address filter;complicated password;Authenticated username and password
IP Camera protocol	ONVIF(Profile S/G/T/M)
Web Viewer	IE10/11 Safari V12.1 above Firefox V.52 above Google chrome V.57 above Edge V.79 above

GENERAL

Operating Temperature	-35~+60°C/less than ≤ 90% RH
Outdoor Ready	IP67
Input Voltage / Current	DC 12V/POE
Power	TBD
Material	Metal

DIMENSIONS



COMPATIBLE ACCESSORIES

CEILING MOUNT SOLUTION



CORNER MOUNT SOLUTION



POLE MOUNT SOLUTION



WALL MOUNT SOLUTION



JUNCTION BOX



DOWNLOAD THE OV CONNECT APP



SECURITY. INNOVATION. RELIABILITY.

POWERED BY G.S.D GROUP INC.

At G.S.D Group, we design and deliver innovative, reliable, and high-performance security solutions that protect people, businesses, and critical infrastructure. From intelligent surveillance and access control to enterprise software and AI-powered technologies, we provide complete security ecosystems built for today's challenges and tomorrow's opportunities.

STAY CONNECTED



 CONTACT US



 YOUTUBE



 LINKEDIN



 NEWSLETTER

COMPLIANCE



CE MARKING



FCC CERTIFICATE



RoHS COMPLIANT



NDAA COMPLIANT

CONNECTION & INTERFACES



HS CODE



UPC CODE



ONVIF COMPLIANT

DOWNLOAD OUR APP: OV CONNECT



WWW.GSDGROUPINC.COM



A CANADIAN ENTERPRISE