

MODEL #

B7T4IP5MP-AI



THERMAL **NETWORK CAMERA**



5MP
RESOLUTION



5MP
Resolution

3.6MM Lens



IR Up to 45M

TotalView



Alarm/Audio
In/Out

Temperature
Measurement



IP67
Dustproof
& Water-Resistant

Micro SD Card
Slot up to 1TB

Discover our **B7T4IP5MP-AI** thermal imaging camera, offering advanced security features. With 5MP resolution, it delivers crystal-clear images, capturing every detail with precision. Two-way communication enables real-time interaction, improving situational awareness. The in/out alarm adds a layer of security by alerting to potential threats. Equipped with temperature measurement capabilities, it goes beyond traditional monitoring by identifying anomalies. The bi-spectrum fusion image offers a unique view by combining thermal imaging with optical channel details. Invest in unrivalled safety with our thermal imaging camera.



THERMAL MODULE

Image Sensor	Vanadium Oxide Uncooled Focal Plane Arrays
Max. Resolution	256×192
Pixel Interval	12µm
Response Waveband	8-14µm
Netd (noise equivalent temperature difference)	≤40mk@25°C F#1.0, 25Hz
Lens (Focal Length)	3.2mm
IFOV	3.75 mrad
Field Of View	56°x42°
Min. Focusing Distance	0.3m
VCA Distance Human	18.6m (61ft)
VCA Distance Vehicle	49m (161ft)
Heat Detection Distance	20m(66ft)
Aperture	F1.1

OPTICAL MODULE

Max. Image Resolution	2592*1944
Image Sensor	1/2.7" Progressive Scan CMOS
Min. Illumination	Color: 0.003 Lux @(F1.6, AGC ON), B/W: 0 @ IR ON
Shutter Speed	1/5 s to 1/100,000 s
Lens (Focal Length)	3.6mm
Field of View	Horizontal: 81°, Vertical: 57°, Diagonal: 108°
WDR	120 dB
Day & Night	IR cut filter with auto switch
BI-Spectrum Image Fusion	Fusion view of thermal view and overlaid details of the optical channel
Supplement Light Type	IR and Warm Light
Supplement Light Range	Up to 30 m (IR) / 15m (Warm light)
IR Wavelength	850nm
Smart Supplement Light	Yes
Warning Light	1 Red & 1Blue flashing light

NETWORK

Main Stream	Visible Light: 50Hz@25fps; 5MP(2592x1944),4MP(2592x1520),3MP(2304x1296), 1080P(1920x1080), 960P(1280*960),720P(1280x720) 60Hz@30fps; 5MP(2592x1944),4MP(2592x1520),3MP(2304x1296), 1080P(1920x1080), 960P(1280*960),720P(1280x720) Thermal: 50Hz/60Hz@25fps; 1280×720, 640x480
Sub-Stream	Visible Light: 50Hz@25fps; 720P(1280x720),VGA(640x480), QVGA(320x240) 60Hz@30fps; 720P(1280x720),VGA(640x480),QVGA(320x240) Thermal: 50Hz/60Hz@25fps; 640 x 480, 320x240
Mobile Stream	Visible Light: 50Hz@25fps; VGA(640x480),QVGA(320x240) 60Hz@30fps; VGA(640x480),QVGA(320x240)
Video Compression	H.265/H.265+/H.264/H.264+MJPEG
Audio Compression	G.711u/G.711a
Protocols	TCPIP,HTTP,DHCP,DNS,DDNS,RTPRTSP,SMTP, NTP,UPnP,SNMP,HTTPS,FTP
User/Host Level	3 users, 2 levels: Administrator, User
Security Measures	User authentication (ID and PW), HTTPS encryption, IP address filtering

INTEGRATION

Alarm Input	1-ch inputs
Alarm Output	1-ch outputs
Alarm Action	SD recording/Alarm output/smart capture/FTP upload/email linkage/ audio alarm/Red & Blue flashing light
Audio Input	1-ch
Audio Output	1-ch outputs/ 1 Built-in speaker
Reset	Yes
Communication Interface	1, RJ45 10M/100M self-adaptive Ethernet interface.
SD Memory Card	Built-in micro SD card slot (up to 1TB)
Analog Video Output (BNC)	NA
Web Browser	IE10/11, Safari V12.1 above, Firefox V.52 above, Google chrome V.57 above, Edge V.79 above

SMART FUNCTION

Temperature Measurement	Global, 12 points, 12 areas, and 12 line.
--------------------------------	---

Temperature Range	-20 °C to + 150 °C (-4 °F to + 302°F)
--------------------------	---------------------------------------

Temperature Accuracy	± 8 °C (± 14.4 °F)
-----------------------------	--------------------

Fire Detection	Yes
-----------------------	-----

AI Features	Optical: Intrusion, Region Entrance, Region Exiting, Line Crossing, Pedestrian & Vehicle, Object Detection, Crossing Counting, Crowd Density, Queue Length, Heat MAP, Rare Sound, Face Detection Thermal: Intrusion, Region Entrance, Region Exiting, Line Crossing detection, Fire detection, Temperature exception alarm, Pedestrian & Vehicle
--------------------	---

GENERAL

Menu Language	English, Russian, German, Italian, French, Portuguese, Spanish, Turkish, Japanese
----------------------	---

Power	12 VDC ± 20%, PoE (802.3af)
--------------	-----------------------------

Power Consumption	Max.10.4W
--------------------------	-----------

Working Temperature/ Humidity	Temperature: -35 °C to 60 °C (-31 °F to 140 °F) ; Humidity: 90% or less
--------------------------------------	--

Protection level	IP67
-------------------------	------


Dimensions	108mm*314.6mm(4.25"*12.39")
-------------------	-----------------------------

Weight	Approx. 1.25kg(2.76lb)
---------------	------------------------

Environment	RoHS2.0
--------------------	---------


DOWNLOAD THE OV CONNECT APP

DIMENSIONS



COMPATIBLE ACCESSORIES

CORNER MOUNT SOLUTION



 **COMB6**
CORNER MOUNT BRACKET

POLE MOUNT SOLUTION



 **PMB6**
POLE MOUNT BRACKET

WALL MOUNT SOLUTION



 **WMB5**
WALLMOUNT BRACKET

OR



 **WMB6**
WALLMOUNT BRACKET

+



 **EB3BASE3-G**
PENDANT

JUNCTION BOX



 **TEBBASE1**
JUNCTION BOX

SECURITY. INNOVATION. RELIABILITY.

POWERED BY G.S.D GROUP INC.

At G.S.D Group, we design and deliver innovative, reliable, and high-performance security solutions that protect people, businesses, and critical infrastructure. From intelligent surveillance and access control to enterprise software and AI-powered technologies, we provide complete security ecosystems built for today's challenges and tomorrow's opportunities.

STAY CONNECTED



 CONTACT US



 YOUTUBE



 LINKEDIN



 NEWSLETTER

COMPLIANCE



CE MARKING



FCC CERTIFICATE



RoHS COMPLIANT



NDAA COMPLIANT

CONNECTION & INTERFACES



HS CODE



UPC CODE



ONVIF COMPLIANT

DOWNLOAD OUR APP: OV CONNECT



WWW.GSDGROUPINC.COM



A CANADIAN ENTERPRISE