

MODEL #

D3F28IP2MP-I-HDMI

CTAVUE®



MINI VANDAL DOME CAMERA WITH HDMI OUTPUT

Onvif® | GSI



5MP
RESOLUTION



2MP
Resolution

2.8MM Lens



IR Up to 20M



Audio
In/Out



DC12V

OR



POE



HDMI Output



Custom
Deterrence
message



IP66
Dustproof
& Water-Resistant



Micro SD Card
Slot up to 1TB

Elevate your security with our new security camera with HDMI output, featuring a 2.8mm lens and 2MP resolution for crystal-clear images. It offers flexible power options with DC 12V or PoE, while its intelligent face detection and customizable deterrence messages enhance security. With audio in/out capabilities, you can communicate seamlessly. Upgrade your surveillance and safeguard your store with confidence.





MINI VANDAL DOME CAMERA

MODEL #

D3F28IP2MP-HDMI

CAMERA

Filter	Removable IR Cut Filter
Image Sensor	1/2.9" 2MP Progressive Scan CMOS
Resolution	1920(H)× 1080(V)
Lens	2.8mm IR Lens
Min. Illumination	0Lux
Electronic Shutter	NTSC:1/30-1/100,000s PAL:1/25-1/100,000s
Available IR Range	15-20M

VIDEO & AUDIO

Video Compression	H.264 / H.265
Transmission Stream Rate	Dual Stream (Code Rate:36Kb~16M)
Frame Rate	1~25fps (PAL) ,1~30fps (NTSC)
Audio Compression	G711A, G711U

EXTERNAL INTERFACE

HDMI 1.4	1080P/30FPS
Network Interface	RJ45*1 10M/100M
Audio Interface	input/output*1
Alarm Interface	input/output*1



NETWORK

Protocol	IPv4, IPv6, DHCP, HTTP, Onvif, DNS, DDNS, FTP, UPNP, RTSP, SMTP, NTP
Network Support	ONVIF Profile S, API
Maximum Users	10
Web Language	English, Simplified Chinese, Traditional Chinese

FUNCTION

Image Setting	Contrast, Brightness, Sharpness, Saturation , WDR, 3DNR, HLC, BLC
Storage	NVR, VMS, TF Card (MAX 1TB)
Video Type	Manual, Timing, Motion Detection, Alarm Video
Alarm Triggers	Motion Detection, Alarm
Alarm Event	Snapshot, Video, Alarm Output, Email Upload
System/explorer Support	IE, Chrome, Firefox, Safari
General Function	Flashing, Mirror, OSD information overlay, Camera angle

GENERAL

Power Supply	DC12V±10%, POE
Current Consumption	570mA (MAX)
Dimension	Ø114× 82mm
Weight	600g
Storage Temperature	-30° ~ +60°
Operating Temperature	-30° ~ +40°
IP Rating	IP67

DOWNLOAD THE OV CONNECT APP



WWW.GSDGROUPINC.COM



A CANADIAN ENTERPRISE

SECURITY. INNOVATION. RELIABILITY.

POWERED BY G.S.D GROUP INC.

At G.S.D Group, we design and deliver innovative, reliable, and high-performance security solutions that protect people, businesses, and critical infrastructure. From intelligent surveillance and access control to enterprise software and AI-powered technologies, we provide complete security ecosystems built for today's challenges and tomorrow's opportunities.

STAY CONNECTED



 CONTACT US



 YOUTUBE



 LINKEDIN



 NEWSLETTER

COMPLIANCE



CE MARKING



FCC CERTIFICATE



RoHS COMPLIANT



NDAA COMPLIANT

CONNECTION & INTERFACES



HS CODE



UPC CODE



ONVIF COMPLIANT

DOWNLOAD OUR APP: OV CONNECT



WWW.GSDGROUPINC.COM  A CANADIAN ENTERPRISE