

MODEL #

XEBFATVIP4MP28-AI-E-B



X SERIES **NETWORK CAMERA**



Introducing the cutting-edge X Series Eyeball security camera, the **XEBFATVIP4MP28-AI-E-B**. This IP camera boasts an impressive 4MP resolution and a 2.8mm lens for crystalclear surveillance footage. With infrared capabilities extending up to 25 meters, coupled with a microphone and speaker for two-way communication, it ensures comprehensive security monitoring. Equipped with deterrence lights and the ability to see in color at night, it provides heightened visibility and deterrence against potential threats. Plus, with an IP67 waterproof rating, it stands strong against the elements, making it the ultimate choice for reliable outdoor security.

This camera model is also available in white - XEBFATVIP4MP28-AI-E

4MP
RESOLUTION



4MP
Resolution

2.8MM Lens



IR Up to 25M

Totalview



Two-Way
Communication

Deterrence
Lights



Microphone
& Speaker

Siren



IP67
Water-resistant
& Dustproof

Micro SD Card
Slot up to 1TB



VIDEO

Image Device	1/3"
Effective Pixels	4MP 2560(H)×1440 (V)
Scanning System	Progressive CMOS
Min. Illumination	Color 0.002 Lux @ (F1.0, AGC ON) ; B/W 0 lux @ IR ON

LENS

Focal Length (Zoom Ratio)	2.8 mm
Max. Aperture Ration	F No. 1.0
Angular Field of View	Horizontal:95°, Vertical:51°, Diagonal: 112°
Min. Object Distance	2m
Lens Type	Fixed (M12)

OPERATIONAL

IR LED	1
Warmlight	2
Red and Blue Light	2 (1 Red & 1 Blue)
IR Viewable Length	Up to 25 m
Warmlight Viewable Length	Up to 20 m
Type of Complementary Light	Default warm light, switchable infrared light
Wide Dynamic Range	DWDR
Digital Noise Reduction	3D DNR
Motion Detection	Off/On (8 Level)
Image Setting	Full Color Mode/Day&Night Mode/Smart Illumination
White Balance	Auto/Manual
Electronic Shutter Speed	1/5 ~ 1/20000s
On-Board Storage	Micro SD slot, up to 1TB
Alarm	Speaker, siren
Audio	Built-in microphone & Speaker
Hardware Reset	Yes
Smart Features	Perimeter Intrusion Detection (PID), Line Crossing Detection (LCD), Intrusion Detection (ID), Region Entry and Exiting

NETWORK

Ethernet	RJ45(10/100BASE-T)
Video Compression Format	H.265/H.264
Resolution	Main Stream@25fps: 4MP(2560x1440) Sub Stream@25fps: VGA(640x480)
Video Quality Adjustment	512Kbps ~ 4Mbps
Bitrate Control Method	CBR/VBR
IP	IPv4
Protocol	TCP/IP, HTTP, DHCP, DNS, DDNS, RTP/RTSP, SMTP, NTP, HTTPS
Security	Complicated password; Authenticated username and password
Application Programming Interface	ONVIF(Profil S/G/T)
Compatible Web Browsers	IE10/11

GENERAL

Operating Conditions	-35°+60°C/ Less than ≤ 95% RH
Ingress Protection	IP67
Input Voltage/ Current	D12V/POE (IEEE802.3af)
Power Consumption	DC12V; max 6.2 W; POE(48V): max 7.5W
Color/Material	Black/Metal
Dimension (LXHXP)	100*100*90mm
Weight	320g

DIMENSIONS



COMPATIBLE ACCESSORIES

CEILING MOUNT SOLUTION



CORNER MOUNT SOLUTION



POLE MOUNT SOLUTION



WALL MOUNT SOLUTION



JUNCTION BOX



DOWNLOAD THE OV CONNECT APP



SECURITY. INNOVATION. RELIABILITY.

POWERED BY G.S.D GROUP INC.

At G.S.D Group, we design and deliver innovative, reliable, and high-performance security solutions that protect people, businesses, and critical infrastructure. From intelligent surveillance and access control to enterprise software and AI-powered technologies, we provide complete security ecosystems built for today's challenges and tomorrow's opportunities.

STAY CONNECTED



 CONTACT US



 YOUTUBE



 LINKEDIN



 NEWSLETTER

COMPLIANCE



CE MARKING



FCC CERTIFICATE



RoHS COMPLIANT



NDAA COMPLIANT

CONNECTION & INTERFACES



HS CODE



UPC CODE



ONVIF COMPLIANT

DOWNLOAD OUR APP: OV CONNECT



WWW.GSDGROUPINC.COM



A CANADIAN ENTERPRISE