

4MP 4 CHANNEL X SERIES IP KIT

ONVIF® | G S T | NDA Compliant | AI



The **XKIT4OVIP4MP-AI-E-B** is a powerful and intelligent surveillance solution designed for maximum security and ease of installation. It includes 4× XEBFATVIP4MP28-AI-E-B cameras and 1× GSD-NVROV6K-04-N network video recorder, ideal for residential and commercial applications.

The cameras deliver clear 4MP video with full-color imaging even in complete darkness. Equipped with active deterrence features such as blue and red lights and a built-in siren, they help prevent intrusions. A built-in microphone and speaker allow for custom voice messages and real-time interaction.

The GSD-NVROV6K-04-N NVR supports up to 12MP recording with 4K HDMI output. Featuring 4 PoE ports with E-PoE, it enables quick and easy installation. With ONVIF compatibility, P2P remote access, and support for up to 20TB storage, it ensures reliable performance.

This kit is also available in white - XKIT4OVIP8MP-AI-E

4MP
RESOLUTION



4MP
Resolution



Two-way
Communication

12MP
RESOLUTION

Up to 12MP
Resolution

ONVIF

ONVIF Compliant
(G/S/T)

4K

4K HDMI Output



Rackmount
Compatible



IR Up to 25M



See in color at
night



Deterrence Lights
& Siren



1HDD slot up to
20TB



1080P VGA
Output



P2P Connection



ONVIF Encoder



X SERIES NETWORK CAMERA

MODEL #

4X XE3FATVIP4MP28-AI-E-B

VIDEO

Imaging Device	1/3"
Effective Pixels	4MP 2560(H)×1440 (V)
Scanning System	Progressive CMOS
Min. Illumination	Color 0.002 Lux @ (F1.0, AGC ON) ; B/W 0 lux @ IR ON

LENS

Focal Length (Zoom Ratio)	2.8 mm
Max Aperture Ratio	F No. 1.0
Angular Field Of View	Horizontal:95°, Vertical:51°, Diagonal: 112°
Min. Object Distance	2m
Lens Type	Fixed (M12)

OPERATIONAL

IR LED	1
Warmlight	2
Red and Blue Light	2 (1 Red & 1 Blue)
IR Viewable Length	Up to 25 m
Warmlight Viewable Length	Up to 20m
Type of Complementary Light	Default warm light, switchable infrared light
Wide Dynamic Range	DWDR
Digital Noise Reduction	3D DNR
Motion Detection	Off/On (8 Level)
Image Setting	Full Color Mode/Day&Night Mode/Smart Illumination
White Balance	Auto/Manual
Electronic Shutter Speed	1/5 ~ 1/20000s
On-Board Storage	Micro SD slot, up to 1TB
Alarm	Speaker, siren
Audio	Built-in microphone & Speaker
Hardware Reset	Yes
Smart Features	Perimeter Intrusion Detection (PID), Line Crossing Detection (LCD), Intrusion Detection (ID), Region Entry and Exiting

NETWORK

Ethernet	RJ45(10/100BASE-T)
Video Compression Format	H.265/H.264/H.265+/H.264+/MJPEG
Resolution	Main Stream @30fps: 4MP(2688x1520),3MP(2304x1296), 1080P(1920x1080) Sub Stream @30fps: 1080P(1920x1080),720P(1280x720), VGA(640x480) Mobile Stream @30fps: VGA(640x480), QVG(320x240)
Video Quality Adjustment	256Kbps ~ 8Mbps
Bitrate Control Method	CBR/VBR
IP	IPv6
Protocol	TCP/IP,HTTP,DHCP,DNS,DDNS,RTP/RTSP, SMTP,NTP,UPnP,SNMP,HTTPS,FTP
Security	IP address filter;complicated password; Authenticated username and password
Application Programming Interface	ONVIF(Profile G/M/S/T)
Compatible Web Browsers	IE10/11, Safari V12.1/above, Firefox V.52/ above, Google chrome V.57/above, Edge V.79/ above

GENERAL

Operating Conditions	-35°+60°C/ Less than ≤ 95% RH
Ingress Protection	IP67
Input Voltage / Current	D12V/POE (IEEE802.3af)
Power Consumption	DC12V; max 6.2 W; POE(48V): max 7.5W
Color/Material	Black/Metal
Dimension (LXHP)	100*100*90mm
Weight	320g





RECORDING BANDWIDTH

Resolution	12MP, 8MP, 5MP, 3MP, 2MP (1080P), 1.3MP (960P), 1.0MP (720P)
Input	76M
Output	76M

PERFORMANCE

Recording Compression	Audio: G.711A,G.711U Video: H.264/H.265/H.264+/H.265+
Speed	4K: 45fps 4MP: 90fps 2MP: 180fps
Playback	1080P: 180fps Max 4ch playback

Network

Remote Connection	Up to 640 Users
WEB	IE10/11, Safari V12.1 above, Firefox V.52 above, Google chrome V.57 above, Edge V.79 above
Protocols	TCP/IP, DHCP, IPv4, IPv6, DNS, DDNS, NTP, RTSP, SMTP, SNMP,UPnP, HTTP, HTTPS
API	Onvif (profile G/S/T)
Voice command	Home Device: Google Assistant, Amazon Alexa

FONCTIONS IA INSTANT NOTIFICATIONS

Human Detection	Region Entrance
Vehicle Detection	Region Exiting
Perimeter Intrusion Detection	Rare Sound Detection
Line Crossing Detection	Stationary Object Detection
License Plate Detection	Crowd Density Detection
Facial Recognition	Heat Map
Intrusion Detection	Noise Detection
Cross-Counting	Video Tampering
Fall Detection	Multi Target Type Detection
Vehicle/Human Attributes	Temperature Measurement
Fire & Smoke Detection	Face Masking
AI MAX CAPTURED QUANTITY 200,000	AI REGISTERED QUANTITY 10,000

INTERFACE

P/W Reset	Yes
VGA	1(1024*768, 1280*720, 1280*1024, 1440*900, 1920*1080)
HDMI	1(1024*768, 1280*720, 1280*1024, 1440*900, 1600*1200, 1920*1080, 1920*1200, 2560*1440(2K), 3840*2160 (4K))/EDID
Ethernet	1 RJ45 100/1000 Base-T
PoE	4*RJ45, 100 Base-T 802.3at/af
USB	USB2.0*1(front) USB2.0*1(rear)
Audio Out	1 out
HDD	1 SATA HDD, up to 20TB
RS485	N/A
Alarm Input/Output	N/A



GENERAL

Language	English/French/Spanish/Portuguese/German/ Italian/Greek/Danish/Finnish/ Russian/ Hebrew/Turkish/Bulgarian/Arabic/Korean/ Japanese/Thai/Hindi/ Romanian/Dutch/Polish/ Persian/Hungarian/Chinese/Ukrainian
Dimension (WxDxH)	300*227*53mm
Weight	≤ 0.98 kg (without HDD, 2.2 lb.)
Input Voltage/Current	48V/1.2A
Power consumption (excluding hard disk)	3.8W
Operating Temperature/ Humidity	Temperature: -10°C~+50°C (14°F ~ 122°F) Humidity: Less than 90%RH
FCC/CE	Yes
Rackmount Compatible	Yes

DIMENSIONS

Length: 227MM | Width: 300MM | Height: 53MM

HDMI[®]
HIGH-DEFINITION MULTIMEDIA INTERFACE



COMPATIBLE HARD DRIVES



WD-HDDPURPLE-1T
UP TO 1TB HARD DRIVE



WD-HDDPURPLE-2T
UP TO 2TB PRO HARD DRIVE

SECURITY. INNOVATION. RELIABILITY.

POWERED BY G.S.D GROUP

At G.S.D Group, we design and deliver innovative, reliable, and high-performance security solutions that protect people, businesses, and critical infrastructure. From intelligent surveillance and access control to enterprise software and AI-powered technologies, we provide complete security ecosystems built for today's challenges and tomorrow's opportunities.

STAY CONNECTED



CONTACT US



YOUTUBE



LINKEDIN



NEWSLETTER

COMPLIANCE



CE MARKING



FCC CERTIFICATE



RoHS COMPLIANT



NDAA COMPLIANT

CONNECTION & INTERFACES



HS CODE



UPC CODE



ONVIF COMPLIANT



4K HDMI Output

DOWNLOAD THE OV CONNECT APP



WWW.GSDGROUPINC.COM A CANADIAN ENTERPRISE