



FENNEC SERIES

BY

MODEL #
GSD-DVRFNC5MP-32-N-AI-16T

32 CHANNEL DIGITAL VIDEO RECORDER

ONVIF®

GST

NDAA
Compliant

Built for high-density surveillance environments, the **GSD-DVRFNC5MP-32-N-AI-24T** is a robust 32-channel AI DVR designed for maximum coverage and control. It supports four hard drives up to 18TB each, advanced AI analytics including crowd density detection, license plate recognition, and intrusion alerts, and delivers smooth system operation with 4K HDMI output. Featuring 16 alarm inputs and 1 alarm output, ONVIF support, and mobile connectivity, this DVR is ideal for enterprise facilities, campuses, and large commercial sites.

5MP
RESOLUTIONUp to 5MP
Resolution LITE

ONVIF

ONVIF Encoder

4K4K HDMI
ResolutionAlarm
16 In/ 1 Out3 HDDs Included
up to 8TB eachSpot Monitor Out
on BNCP2P Mobile
ConnectionUp to 4 IP
Cameras

AI FEATURES

- Human & Vehicle Detection
- Perimeter Intrusion Detection
- Line Crossing Detection
- License Plate Detection
- Facial Recognition
- Intrusion Detection
- Queue Length Detection
- Region Entry And Exit
- Cross-Counting
- Rare Sound Detection
- Stationary Object Detection
- Crowd Density Detection
- Heat Map
- Noise Detection
- Video Tampering

WWW.GSDGROUPINC.COM



A CANADIAN ENTERPRISE



FENNEC SERIES

BY



MODEL #

GSD-DVRFNC5MP-32-N-AI-24T

LIVE

IP Video Input	4ch
Composite Video Input	up to 36ch (Analog video + IP video)

PERFORMANCE

Compression	Audio: G.711a Video : H.264/H.265
Display Resolution	Analog : 5MP-Lite (1280x1944) @15fps 4MP-Lite @30 fps 1080P/720P/960H @ 30fps
Speed	Analog : 5MP-Lite:15fps (each ch) 4MP-Lite:20fps(each ch) 1080P:15fps(each ch) 720P:PAL:25fps(each ch)/NTSC:30fps(each ch) IP: PAL:25fps(each ch)/NTSC: 30fps(each ch)
Ai Features	PID - Perimeter Intrusion Detection LCD - Line Crossing Detection PD&VD - Human&Vehicle Detection FD - Face Detection FR - Face Recognition
Event	MD (Sensitivity Level 1~8) VIDEO LOSS Beep, Email, Push notification to Mobile APP
Playback Function	Fast forward / backward (2x, 4x, 8x,16x) Slow forward (1/2x, 1/4x, 1/8x,1/16x)
Playback	5MP-lite: 240fps (Max 16CH playback) 4MP-lite: 320fps (Max 16CH playback) 1080P: 480fps (Max 16CH playback) 720P:960fps (Max 16CH playback)

FONCTIONS IA INSTANT NOTIFICATIONS

Human Detection	Region Exiting
Vehicle Detection	Cross-Counting
Perimeter Intrusion Detection	Rare Sound Detection
Line Crossing Detection	Stationary Object Detection
License Plate Detection	Crowd Density Detection
Facial Recognition	Heat Map
Intrusion Detection	Noise Detection
Region Entrance	Video Tampering
Queue Length Detection	INSTANT NOTIFICATIONS
AI MAX CAPTURED QUANTITY 200,000	AI REGISTERED QUANTITY 10,000

*THESE AI FEATURES ONLY WORK WITH IP CAMERAS, OR ANALOG CAMERAS WITH 2MP OR MORE

RECORDING BANDWIDTH

Inputs	16Mbps
Out	216Mbps
Analog-video-input	32CH inputs

UI/MONITORING

Local	UI5.0
Web	IE10/11 / Safari V12.1 above / Firefox V.52 above Google chrome V.57 above / Edge V.79 above
Mobile Viewer	OV connect
Push Notification	Yes

INTERFACE

P/W Reset	Factory Reset : Press 10 seconds
BNC	1 (704*576)
VGA	1(1024*768, 1280*720, 1280*1024, 1440*900, 1920*1080)
HDMI	1(1024*768,1280*720,1280* 1024,1440*900,1920*1080,25 60*1440(2K),3840*2160(4K))
Ethernet	2 RJ45 100/1000 Base-T
USB	USB2.0*1(front) / USB3.0*1+(rear)
Audio	8 in /1 out
E-SATA	1
HDD	4 SATA HDD, Up to 18 TB capacity for each disk, 3 HDDs Included up to 8TB each
RS485	1
Alarm Input/Out	16 in /1 out

GENERAL

OSD Language	English/French/Spanish/Portuguese/ German/Italian/Greek/Danish/Finnish/ Russia/Hebrew/Turkish/Bulgarian/Arabic/ Korean/Japanese/Thai/Hindi/Romanian/ Dutch/Polish
Dimension (WDXH)	380*340*50mm
Input Voltage/Current	DC12V/5A
Power Consumption (Excluding Hard Disk)	21W
Operating Temperature/ Humidity	Temperature : -10°C~+50°C (14°F ~ 122°F) Humidity : Less than 90%RH






FENNEC SERIES

BY



MODEL # **GSD-DVRFNC5MP-32-N-AI-24T**

DIMENSIONS



Length:317.4MM | Width:378MM | Height: 50MM



COMPATIBLE ACCESSORIES



BALUNHDA+

VIDEO/POWER/AUDIO OVER CAT5

DISTANCE	400+
FORMAT	PIGTAIL
DETAILS	VIDEO POWER AUDIO
PACKAGE	PAIR
TECHNO	TVI/CVI/AHD/ANALOG




BALUNHD

BALUNHD OVER TWISTED PAIR

DISTANCE	700+ FEET
FORMAT	PIGTAIL
DETAILS	2MP/5MP/8MP
PACKAGE	PAIR
TECHNO	TVI/CVI/AHD/ANALOG



SWC5POE-GIGA
POE SWITCH



SWC5POE-MAN
POE SWITCH



WD PURPLE PRO
UP TO 2TB HARD DRIVE



WD PURPLE PRO
UP TO 4TB HARD DRIVE



WD PURPLE PRO
UP TO 8TB HARD DRIVE



SECURITY. INNOVATION. RELIABILITY.

POWERED BY G.S.D GROUP INC.

At G.S.D Group, we design and deliver innovative, reliable, and high-performance security solutions that protect people, businesses, and critical infrastructure. From intelligent surveillance and access control to enterprise software and AI-powered technologies, we provide complete security ecosystems built for today's challenges and tomorrow's opportunities.

STAY CONNECTED



 CONTACT US



 YOUTUBE



 LINKEDIN



 NEWSLETTER

COMPLIANCE



CE MARKING



FCC CERTIFICATE



RoHS COMPLIANT



NDAA COMPLIANT

CONNECTION & INTERFACES



HS CODE



UPC CODE



ONVIF COMPLIANT

DOWNLOAD OUR APP: OV CONNECT



WWW.GSDGROUPINC.COM  A CANADIAN ENTERPRISE